

SEALING FAST

MODIFIED BITUMEN BASED TWO COMPONENT SEALANT

SEALING FAST is a modified bitumen based two component sealant. When the components are mixed, a special hardening reaction takes place that causes the sealant to harden in a short time. SEALING FAST is safe, easy to apply and can be used at outdoor temperatures between 5 and 30 °C. Unlike with hot sealants, no thermal shock occurs at lower temperatures with Sealing Fast, such as when applied to cold road surfaces.

SEALING FAST can be used to seal cracks on the floor of bituminous concrete or of concrete and restore expansion joints.

The product can be applied in three different ways:

- with Sealing Set Evo or Sealing Set Pro, a special sealing machine developed by us;



cold crack seal no





Preparation of the surface to be sealed is extremely important for successful sealing. In cases where the crack has a width of less than 1 cm, it is advisable to carry out its widening with a special milling cutter, thanks to which it is possible to create a channel that allows the sealant to adequately close the crack. In addition, the milling cutter is equipped with a mechanism that sucks up the material and dust formed during milling.





SEALING 5750 cold crack sealing

- **Sealing Fast SC**, in cartridges (950 gr) to be applied manually;







SEALINGFAST WH cold crack sealing

- **Sealing Fast WH**, kit (4,8 kg) to be applied manually to create a micro-carpet with the addition of Pro Patch cold bituminous con-














FORM TECHNICAL FEATURES



PENETRATES DEEP INTO CRACKS



EASE OF USE



EXCELLENT
ADHESION TO THE
EXISTING ROAD
SURFACE



VOLATILE SOLVENT FREE



LOGISTICAL
ADVANTAGES OF
COLD TECHNOLOGY



RESISTANT TO LOW AND HIGH TEMPERATURES



APPLIED WITHOUT THE USE OF HEAT



HIGHLY ELASTIC



RESISTANT TO HYDROCARBONS



Edilpavimentazioni Srl

Via Bolzano 2-4, 38015 Lavis (TN) +39 0461 870645 info@viatek.pro info@edilpavimentazioni.it www.viatek.pro